

PowerGem

Load Shedding? Not On Our Watch.

/// FEATURES

1C
Continuous Power

10
Year Warranty

32
Units Stackable

⚙️ NEAT

10 year warranty
Ultra safe LFP material
Elegant enclosure design
Floor-standing / wall-mounting

👉 HANDY

Quick installation
Remote monitoring
Flexible remote upgrade
Auto-addressing for master / slaves set up

⚙️ ROBUST

Parallel up to 32 modules
Wide range inverter compatibility
1C rate continuous charge/discharge
Multi protection to avoid over discharge
Smart BMS management for longer lifespan
Active balancing charging, low self consumption





Model	PowerGem
Cell Type	LFP
Rated Power	5.12kWh
Rated Capacity	100Ah
Rated Voltage	51.2V
Charge Voltage	56.5V
Max Charge/Discharge Current	100A
Discharge Peak Current	105A / 15s, 120A / 0.5s
Parallel	Up to 32 units parallelable w/o extra device needed, slave battery drops offline or come back alive does not affect system running
IP Level	IP20
Dimension	640*428*166mm
Weight	58Kg
Communication	CAN/RS485
Compatible Inverter	Victron, Luxpower, Deye, Voltronic, SMA Goodwe, Growatt, Sofar, Solark, SRNE, Must
Humidity	5%~85% RH (No condensation)
Work Temperature	-20 °C ~ +55 °C
Storage Temperature	-10 °C ~ +35 °C
Remote Maintenance	Flexible remote upgrade, remote monitoring Original firmware backup to prevent upgrade failure
Warranty *	10 year, 6000 cycles
Certification	CE UN38.3 IEC62619
Protection	Over charge/discharge/current/voltage/temperature protection Short circuit protection, Reverse connection protection Stronger active balance, Low SOC protection